

# ComColor FT 5000

Ultra High-Speed  
Full-Color Inkjet Printers



## ULTRA-FAST

full-color printing



A feature-rich lineup that is  
**environmentally-  
friendly**

### Full-color Letter printing



Print speed  
108 ppm



Print size  
Letter



CMYK  
Full color



3 trays



Low energy  
consumption



Environmental  
certification

## ComColor FT 5000 Specifications

Print Type		Line-type inkjet system
Ink Type		Oil-based pigment ink (Cyan, Magenta, Yellow, Black)
Print Resolution		Standard: 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction) Fine: 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)
Number of Gray Levels		For each CMYK color (11 gray levels)
Data Processing Resolution		Standard: 300 dpi × 300 dpi Fine: 600 dpi × 600 dpi Line smoothing: 600 dpi × 600 dpi
Warm-up Time		2 min. 30 sec. or less (at room temperature of 73.4°F (23°C))
First Print Time *1		5 sec. or less (A4)
Continuous Print Speed *2	Letter	Simplex: 108 ppm Duplex: 54 sheets/minute (108 ppm)
	A4	Simplex: 100 ppm Duplex: 50 sheets/minute (100 ppm)
	Legal	Simplex: 92 ppm Duplex: 42 sheets/minute (84 ppm)
Paper Size	Standard Tray	Maximum: 13 3/8" × 21 5/8" (340 mm × 550 mm) *3 Minimum: 3 9/16" × 5 27/32" (90 mm × 148 mm)
	Feed Tray	Maximum: 11 11/16" × 17" (297 mm × 432 mm) Minimum: 7 3/16" × 7 3/16" (182 mm × 182 mm)
Printable Area		Maximum: 8 1/4" × 21 13/32" (210 mm × 544 mm)
Guaranteed Print Area *4		Standard: Margin width of 7/32" (5 mm) Maximum: Margin width of 1/8" (3 mm)
Paper Weight	Standard Tray	Simplex: 12-lb bond to 56-lb bond (46 gsm to 210 gsm) *5 Duplex: 12-lb bond to 56-lb bond (46 gsm to 210 gsm) for Letter and A4 / 12-lb bond to 28-lb bond (46 gsm to 104 gsm) for Ledger, A3, Legal, B4 (JIS)
	Feed Tray	Simplex/Duplex: 14-lb bond to 28-lb bond (52 gsm to 104 gsm)
Paper Tray Capacity	Standard Tray	Height up to 4 5/16" (110 mm)
	Feed Tray	Height up to 2 3/16" (56 mm) (2 trays)
Output Tray Capacity		Height up to 2 3/16" (56 mm)
Page Description Language		RISORINC/C IV
Supported Protocols		TCP/IP, HTTP, HTTPS (TLS), DHCP, FTP, LPR, IPP, SNMP (SNMP v1), Port 9100 (RAW port), IPv4, IPv6, IPSec (IKEv1)
Supported Operating Systems	Standard	Microsoft®: Windows®, Windows Server® *6
	Optional *7	Mac: macOS *6 Linux®: Compatible with PPD only
Network Interface		Ethernet 1000BASE-T/100BASE-TX/10BASE-Tx2 Channel
Memory Capacity		4 GB
Hard Disk *8	Capacity	500 GB
	Available Space	Approx. 430 GB
Operating System		Linux
Power Source		AC 100-240 V, 10.0-5.0 A, 50-60 Hz
Power Consumption		Max. 1,000 W Ready *9: 95 W or less Sleep *10: 2 W or less Stand-by: 0.4 W or less
Operating Noise		64dB (A) or less at printing
Operating Environment		Temperature: 59°F to 86°F (15°C to 30°C) Humidity: 40% to 70% RH (non-condensing)
Dimensions (W x D x H)		In use: 40 19/32" × 28 15/16" × 43 29/32" (1,030 mm × 735 mm × 1,115 mm) With cover and tray closed: 30 17/32" × 27 15/16" × 38 7/32" (775 mm × 710 mm × 970 mm)
Weight		Approx. 297 lb (135 kg)
Dimensions When Operating (W x D x H)		With the front cover open and the operation panel in the upright position: 46 21/32" × 48 7/32" × 43 29/32" (1,185 mm × 1,225 mm × 1,115 mm)
Accessories		Scanner HS7000, Face Down Finisher F10, Multifunction Finisher FG20/Folder Unit FG20, Auto-Control Stacking Tray II, Wide Stacking Tray, ComColorExpress RS1200C, PS Kit FG10, IC Card Authentication Kit II, Envelope Feed Kit, Card Feed Kit

Specifications are subject to change without notice.

\*1 Within 10 minutes after the last print job.

\*2 When using plain paper and recycled paper 23-lb bond (85 gsm), and standard density setting. Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)].

The continuous print speed varies depending on the type of optional output equipment connected.

Face Down Finisher: Without offset: 100 sheets/minute (Letter-LEF /A4-LEF Simplex), Offset output: 82 sheets/minute (Letter-LEF /A4-LEF Simplex).

\*3 When using duplex print: 13 3/8" × 18 1/8" (340 mm × 460 mm).

\*4 The guaranteed area when printing images is the area enclosed within 7/32" (5 mm) of the edges of the paper. The margin when printing envelopes is 3/8" (10 mm).

\*5 Duplex printing is not guaranteed with thick paper the weight of which is greater than 28-lb bond (104 gsm).

\*6 For the OS version, please see the RISO Website or contact your local sales representative.

\*7 Optional PS Kit FG10 or ComColor Express RS1200C is required.

\*8 One gigabyte (GB) is calculated as 1 billion bytes.

\*9 Without printing and temperature adjustment operation.

\*10 When setting [Power Consumption (in sleep)] to [Low].



### ComColor FT Ink Cartridges

Colors: Black, Cyan, Magenta, Yellow

#### Environmental Certifications



RISO, and ComColor are trademarks or registered trademarks of RISO KAGAKU CORPORATION. Mac and macOS are trademarks of Apple Inc. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.



**RISO LATIN AMERICA, INC.**

13680 NW 5<sup>th</sup> Street, Suite 100 - Sunrise, FL 33325  
https://www.risolatin.com/